


# MA325 PCB Terminal Block, Modular



## DIMENSIONS/POSITIONS

DIMENSIONS/POSITIONS		MA325-500M	MA325-508M
間距	Pitch	5.00mm	5.08mm
位數	Poles	2 ~ 3Poles	2 ~ 3Poles
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Stainless Steel	Stainless Steel
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
螺紋	Screw Thread	M2.6, Steel, Zinc Plated	M2.6, Steel, Zinc Plated
電線線徑	Wire Size	18 ~ 22AWG	18 ~ 22AWG
剝線長度	Wire Strip Length	4.5mm ~ 5.5mm	4.5mm ~ 5.5mm
PCB孔徑	PCB Hole Diameter	1.6mm	1.6mm
最大緊固扭矩	Tightening Torque, Max.	4.0 Lb-in	4.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

## TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I <sub>n</sub>	Nominal Current I <sub>n</sub>	10A	10A
額定橫截面	Nominal Cross Section	0.75mm <sup>2</sup>	0.75mm <sup>2</sup>
最大負載電流	Maximum load current	10A	10A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		300V	300V
額定電流,UL/CUL Nominal current, UL/CUL		10A	10A

