



# ME260 Male Connector, Double Level Header with Flanges **DECA**<sup>®</sup>



ME260-381



ME260-500



## DIMENSIONS/POSITIONS

DIMENSIONS/POSITIONS		ME260-381	ME260-500
間距	Pitch	3.81mm	5.00mm
位數	Poles	4 ~ 32Poles	4 ~ 48Poles
塑膠本體	Housing Material	PBT	PA 66
焊針	Pin Dimensions	Brass, Tin Plated	Brass, Tin Plated
PCB孔徑	PCB Hole Diameter	1.3mm	1.5mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

## TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I <sub>N</sub>	Nominal Current I <sub>N</sub>	10A	12A
額定橫截面	Nominal Cross Section	-	-
最大負載電流	Maximum load current	10A	12A
絕緣材料	Insulating Material	PBT	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		300V	300V
額定電流,UL/CUL Nominal current, UL/CUL		10A	16A

