


MWX801 PCB Spring Type Terminal Block



DIMENSIONS/POSITIONS		MWX801-635M	MWX801-952M
間距	Pitch	6.35mm	9.52mm
位數	Poles	2 ~ 24Poles	2 ~ 24Poles
塑膠本體	Housing Material	PA 66	PA 66
側蓋	Cover	PA 66	PA 66
中柱	Lever	PA 66	PA 66
端子	Contact	Copper, Tin Plated	Copper, Tin Plated
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
電線線徑	Wire Size	10 ~ 20AWG	10 ~ 20AWG
剝線長度	Wire Strip Length	11mm	11mm
PCB孔徑	PCB Hole Diameter	1.7mm	1.7mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I _n	Nominal Current I _n	25A	25A
額定橫截面	Nominal Cross Section	-	-
最大負載電流	Maximum load current	25A	25A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		300V	300V
額定電流,UL/CUL Nominal current, UL/CUL		25A	25A

