


SDUS1.5-B



目錄僅供參考，實際規格仍依照產品工程圖面為準

產品介紹 Product Description


標準法規 Standards and Regulations

IEC 連接數據 IEC Connection data (60947-7-1) CE	
額定電壓 (V) Rated voltage (V)	400
額定電流 (A) Rated current (A)	17.5
導線橫截面積 (mm ²) Conductor cross section (mm ²)	0.2mm ² ~ 1.5mm ²
CSA 連接數據 CSA Connection data	
額定電壓 (V) Rated voltage (V)	300
額定電流 (A) Rated current (A)	15
線徑範圍 (AWG) Wire Range (AWG)	28~16
UL 連接數據 UL Connection data	
額定電壓 (V) Rated voltage (V)	300
額定電流 (A) Rated current (A)	10
線徑範圍 (AWG) Wire Range (AWG)	28~16
CUL 連接數據 CUL Connection data cUL[®]us	
額定電壓 (V) Rated voltage (V)	300
額定電流 (A) Rated current (A)	10
線徑範圍 (AWG) Wire Range (AWG)	28~16

商務資料 Key Commercial Data

包裝單位 Packing unit	1 PCS
MOQ Minimum order quantity	25 PCS
條碼GTIN	
產品重量 Weight per Piece (excluding packing)	1.57 g
訂貨碼 Custom tariff number	
原產地Country of origin	CN

材料資訊 Material information

絕緣材料 Insulating material	PA66
符合UL 94的可燃性等級 Flammability rating according to UL 94	V0
產品顏色 Color	
最大工作溫度 °C Continuous operating temp., max.	105°C
最小工作溫度 °C Continuous operating temp., min.	-40°C

外型尺寸 Dimensions

寬度 Width	25 mm
長度 Length	5 mm
高度 Height	17.2 mm

一般資訊 General information

產品連接數 Number of connections	2
產品電位 Potentials	1
安裝指導 Installation Advice	Without push-buttons; with fixing flange; for screw or similar mounting types ;fixing hole 3.2mm ϕ 帶有固定耳，適用於螺絲或類似安裝類型，固定孔3.2mm ϕ
應用領域 Area of application	機電工程
	能源工程
	機械工程
	運輸工程
	自動工程
額定浪湧電壓 Rated surge voltage	6 Kv
汙染程度 Degree of pollution	3
過電壓類別 Overvoltage category	III
絕緣材料組 Insulating material group	I
側邊為開放式 Open side panel	yes
手背防護 Back of the hand protection	guaranteed
手指保護 Finger protection	guaranteed

連接數據 Connection data

連接 Connection	1
連接方式 Connection method	Cage clamp
撥線長度 Stripping length	8~9 mm
針對管狀端頭 H1/10 和 H1.5/10 須應用的剝線長度 For the wire end ferrules H1/10 and H1.5/10 of stripping length is to apply.	8~9 mm
導線連接截面積，多股導線，帶管狀端頭 DIN 46228/1 Wire connection cross-section, stranded conductor with wire-end ferrules DIN 46228/1	1.5 mm ²
導線連接截面積，多股導線，帶管狀端頭 DIN 46228/4 Wire connection cross-section, stranded conductor with wire-end ferrules DIN 46228/4	1.5 mm ²
螺絲刀口尺寸 Blade size	0.5 x 3mm

環保產品合規 Environmental Product Compliance

China RoHS	
------------	--

RoHS
Compliant